



GETTS

Generator. ECU. Tent. Trailer. SteriSpace.



About the Product

A state-of-the-art air sterilization and Turnkey solution designed and developed to destroy airborne biological contaminants including pathogens, vegetative bacteria, viruses and allergens from a continuous volume airflow.

Why Choose Us

Modular Design – Built for quick deployment and flexible configuration in various combat or emergency scenarios, with:



Generator

A trailer-mounted generator for electrical power, essential for operating GETTS in remote or off-grid locations.



Environmental Control Unit (ECU)

A trailer-mounted ECU for cooling/heating, complete mobility.



Steel Deck Trailer

A durable platform for transporting and housing the system, enabling quick setup and mobility.



SteriSpace Unit (200 CFM)

A sterile air unit that provides clean airflow at 200 CFM engineered for deployment in medical facilities, clean room environments, or field shelters where biological threats and strict air purity standards are critical.



A tent / shelter is available upon request, with dedicated storage space for it included within the trailer.

Features

Rapidly deployable mobile system:

Built for quick setup in emergency or time-sensitive situations.

Effective containment and isolation:

Controls airborne infections and biological contaminants in challenging conditions.

Exceptional pathogen elimination:

Achieves 99.9999% (6-log) destruction of airborne pathogens, viruses, and allergens.

Built for high-risk scenarios:

Ideal for biological warfare zones and infectious outbreaks in austere or remote locations.

Rapid air sterilization:

Delivers fast-acting sterilization through high-speed destruction of airborne particles.

Filter-free operation:

No filters required—minimizing maintenance and ongoing costs.

Electrical Safety:

Watertight, UL/CSA/NEC/NFPA 70 E Compliant cables and electrical disconnect

Resilient system:

Supports hospitals and healthcare systems during patient surges or crises.

Contact Us



716-204-7215
866-496-2831



www.sterispacesystems.com
info@youfirstservices.com



Trailer Total Weight : 4837 lbs. (with out Fuel)

Optional : Cold Weather Package (Includes Block Heater and Battery Heater)

Gross Vehicle Weight Rating : 7000 lbs.

SPECIFICATIONS



Generator

- **POWER OUTPUT RECEPTACLES:** (2) 60 Amp 3-phase, 5 Pin, Switch Rated.
(1) 30 Amp, 3-Phase, 5 Pin, Switch Rated.
- **FINGER-SAFE/ARC-FLASH COMPLIANT:**
(2) 60 Amp, 120/208 VAC, 5 Pin Power Cable, 40'.
(1) 30 Amp, 120/208 VAC, 5 Pin Power Cable, 20'.
- **OPERATING POWER:** 35 KW/38 KVA 120/208 VAC, 3 phase, 4 wire system.
- **FUEL TANK CAPACITY:** 77 Gallon Diesel Fuel Tank, 24 hour fuel supply.
- **START-UP POWER:** Battery with charger.
- **NOISE LEVEL:** 67 dB.
- **GROSS WEIGHT:** 1,397 lbs.



Environmental Control Unit

- **POWER REQUIREMENTS:** 208V-400V/1-Phase - 3 - phase/50 Hz - 60 Hz.
- **AIR FLOW:** 1200 CFM @ 0.1" WC Conditioned.
- **POWER RECEPTACLE:** 60 AMP, 5 Pin, Switch Rated Plug/Disconnect.
- **OPERATING TEMPERATURE:** -40° F/- 40° C to +124° F/+51°.
- **DIMENSIONS:** 42.50 in. x 34.25 in. x 27.00 in.
- **DUCTING:** (2) 12" Supply/ Return Ducts.
- **COOLING CAPACITY:** 36,000 BTU/HR. @ 95° F.
- **HEATING CAPACITY:** 27,300 BTU/HR.
- **REFRIGERANT:** R407C/R410A.
- **WEIGHT:** 400 lbs.



Steel Deck Trailer

- **OVERALL DIMENSIONS:** 86"w x 264"d x 75"h.
- **STEEL DECK:** 7' x 18'.
- **COUPLER HEIGHT:** 17".
- **STORAGE:** Setback jack, spare tire carrier, space for tent.
- **PAYLOAD RATING:** 5060 lbs.
- **BRAKING:** Sealed Brake Connections.
- **FRAME COUPLER:** 2-15/16 in. A-Frame.
- **TRAILER CONNECTIONS:** 7-Way RV-Style Electrical Connector.
- **WEIGHT:** 1940 lbs.



SteriSpace Unit (200 CFM)

- **OVERALL DIMENSIONS:** 68.5" L x 51" w x 55" H, Base is 40" x 50".
- **AIRFLOW:** 200 CFM at High Suction Power.
- **POWER SUPPLY REQUIREMENTS:** 208-230 VAC, 60 Hz, 40 Amp, 3 Phase.
- **OPERATING REQUIRED POWER:** 3.4 KW.
- **POWER RECEPTACLE:** 60 AMP, 5 pin, Switch Rated plug/Disconnect.
- **WEIGHT:** 1000 lbs.
- **OTHER FEATURES:** 16 Gauge Steel Enclosure. Military Grade Powder Coat Paint Finish. Lockable NEMA 3R Control Panel. Lockable NEMA 4X Cover Over Control Components.

Contact Us

MADE IN BUFFALO, U.S.A. 

716-204-7215

866-496-2831

